





tallation

#### > Sailboat > 55'













### FXH<sup>2</sup>: COMPACT & DUAL DIRECTION CONTROL HYDRAULIC FURLER

- ① Hydraulic watertight motorization in C&N aluminum unit + Furling in/Out control
- 2 Titanium toggle: adaptated to high load and numerous rotations
- Protection cover with handle: that eases the fixation on deck
- Male & female couplings for quick connect fittings (flexible cable not delivered)
- (5) Articulated stand-up toggle in S/steel fitted with quick-release pin: compulsory fitting on deck padeye

# **OPTIONS** accordingly to sailboat configuration:

- **Micro power pack** with receiver & ⑦ **integrated radio control** (wired plugging possible)
- (8) Through deck fitting: making easy the deck hydraulic installation 2-to-1 snatch block available for halyard swivel

## THE FXH<sup>2</sup> ADVANTAGES:

- > Compact: easy switch from manual to hydraulic furler > Adaptable to Asym. Spinnaker/Code Sails
- > Furling In/Out control: in both rotation directions
- > Effortless Sailing: quick furling, comfortable handling from cockpit in shorthanded crew

Retail price : Hydraulic furler kit from 8500€ (ex VAT)

### TECHNICAL DATA

BOAT LENGTH	MODEL	CODE SAIL MAX AREA	FURLING SPEED	Optimal PRESSURE	ø E	DIMENSIONS (mm) A B C		
			(rpm)	/ Max	(mm)	_	ь	
<b>55 &lt; 62'</b> 12 < 18 m	FXH <sup>2</sup> 7000	250 m <sup>2</sup>	114 rpm / 8 l. min	100 bars 140 bars max	14	228	195	245
<b>+62′</b> +18 m	FXH <sup>2</sup> 9000 FXH <sup>2</sup> 12000				18			



